



# Electric Chain Hoists

Compact, Heavy Duty, Competitively Priced

Japanese Technology  
 Load limited  
 Thermal overload prevention  
 Emergency Stop button

## Electric Chain Hoists 3-phase

- Load Limited
- Thermal overload prevention
- Lightweight, compact design with high efficiency motor
- Pressed steel structure, high strength body
- High tensile alloy steel top & bottom hooks
- Grade 80 - Alloy Steel load chain
- Limit switches fitted at top and bottom ends to prevent chain runout
- 415V, 50Hz Dual speed Motor (3 Phase)
- Complies with ASNZS1418.2 standard

\* Hoists can be re-chained to your required length (limits apply)

Models	0103	0106	0303	0503
Dimension (mm)				
A	582	670	670	
B	280	313	313	
D	300	430	430	
E	176	265	325	
H	650	845	1030	
I	40	58	60	
J	31	47	48	
K	40	58	60	
L	31	47	48	
M	22	36	43	
N	22	36	43	



IP Rating  
 Hoist: IP54  
 Control: IP65



3-phase, 415v, 50Hz (dual speed)										
Model	Capacity ton	Standard Lift M	Running Test Load kN	Motor Power (kW)	No. of Chain	Dia of Chain mm	Lifting Speed (m/min)	Net Weight kg	Extra weight per metre of extra lift kg	
TECH-3PH-2SP-0103	1	3	12.5	1.2	1	7.1	1.2/3.5	61	2.2	
TECH-3PH-2SP-0106	1	6	12.5	1.2	1	7.1	1.2/3.5	68	2.2	
TECH-3PH-2SP-0303	3	3	35.7	3.0	1	11.2	5.4/1.8	122	2.8	
TECH-3PH-2SP-0503	5	3	62.5	3.0	2	11.2	2.7/0.9	151	5.6	



email: sales@garrickherbert.com.au  
 Phone: 02 9545 6633  
 web: www.garrickherbert.com.au